



\* DC FILE COPY



APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED





BY

WSMR METEOROLOGICAL TEAM



ATMOSPHERIC SCIENCES LABORATORY WHITE SANDS MISSILE RANGE, NEW MEXICO

ECOM
UNITED STATES ARMY ELECTRONICS COMMAND

5013

SECURITY CLASSIFICATION OF THIS PAGE (Then Date Ente

REPORT DOCUMENTATIO	N PAGE	READ INSTRUCTIONS 3EFORE COMPLETING FORM
DR-946	2. GOVT ACCESSION NO.	3. RECIPIENT'S CATALOG NUMBER
4. TITLE (and Bubello) 14821A Lance Missile No. 3294, Round No. 30	1 APL	S. TYPE OF REPORT & PERIOD COVERED
		6. PERFORMING ORG. REPORT HUMBER
7. AUTHOR(4)		8. CONTRACT OR GRANT NUMBER(s)
WSMR Meteorological Team		DA Task 1T665702D127402
PERFORMING ORGANIZATION NAME AND ADDRE	116	10. PROGRAM ELEMENT, PROJECT, TASK AREA & WORK UNIT NUMBERS
1. CONTROLLING OFFICE NAME AND ADDRESS		12. REPORT DATE
US Army Electronics Command	L	October 1977
Atmospheric Sciences Laboratory	y	13. NUMBER OF PAGES
White Sands Missile RAnge, New	Mexico	40
14. MONITORING AGENCY NAME & ADDRESS(II ditte	erent from Controlling Office)	18. SECURITY CLASS. (of this report)
US Army Electronics Command		
Ft. Monmouth, New Jersey		INCLASSIFIED  15a, DECLASSIFICATION/DOWNGRADING SCHEDULE

APPROVED FOR PUBLIC RELEASE; DISTRIBUTION UNLIMITED.

17. DISTRIBUTION STATEMENT (of the chetreet entered in Block 20, If different from Report)

18. SUPPLEMENTARY NOTES

19. KEY WORDS (Continue on reverse side if necessary and identify by block number)

- 1. Ballistics
- 2. Meteorology
  - 3. Wind

26. ABSTRACT (Continue on reverse side if resessory and identify by block number)

Meteorological data gathered for the launching of 14821A Lance, Missile No. 3294, Round No. 301 APL, are presented in tabular form. BLANK PAGE

SECURITY CLASSIFICATION OF THIS PAGE(When Date Entere

### CONTENTS

INTRODUC	CTION
DISCUSSI	ON
TABLES	
ı.	Surface Observations taken at LC-39
II.	Pilot-Measured-Balloon Wind Data, Release No. 3 at 1123 HRS MDT
III.	Pilot-Measured-Balloon Wind Data, Release No. 4 at 1133 HRS MDT
IV.	WSD Significant Level Data (Release Time: 1045 HRS MDT)
v.	WSD Upper Air Data (Release Time: 1045 HRS MDT)
VI.	WSD Mandatory Levels (Release Time: 1045 HRS MDT)
VII.	Stallion Significant Level Data (Release Time: 1129 HRS MDT)
VIII.	Stallion Upper Air Data (Release Time: 1129 HRS MDT)
IX.	Stallion Mandatory Levels (Release Time: 1129 HRS MDT)
x.	Jallen Significant Level Data (Release Time: 1130 HRS MDT)
XI.	Jallen Upper Air Data (Release Time: 1130 HRS MDT)
XII.	Jallen Mandatory Levels (Release Time: 1130 HRS MDT)

ACCESSION for	
NTIS DDC UNANNOUNCED JUSTIFICATION	White Section Buff Section
	VARIABILITY CODES
Dist. AVAIL	and/or SPECIAL
A	

#### INTRODUCTION

14821A Lance, Missile Number 3294, Round Number 301 APL, was launched from LC-39, White Sands Missile Range (WSMR), New Mexico, at 1129 HRS MDT, 5 October 1977. The scheduled launch time was 1115 HRS MDT.

#### DISCUSSION

Meteorological data were recorded and reduced by the WSMR Meteorological Team, Atmospheric Sciences Laboratory (ASL), WSMR, New Mexico. The data are presented in the following tabulations.

ELEVATION	4,063.75	FEET/MSI
PRESSURE	881.0	MBS
TEMPERATURE	25.0	*c
RELATIVE HUMIDITY	68	z
DEW POINT	18.7	*c
DENSITY	1,021	GM/M <sup>3</sup>
WIND SPEED	03	мрн
WIND DIRECTION	200	DEGREES
CLOUD COVER	5	Cu Ac
OLOUD COTER	3	Ci

TABLE I. SURFACE OBSERVATIONS TAKEN AT LC-39, 1128 HRS MDT/5 OCTOBER 1977.

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)	HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
SUR	200	3.0	2100	210	3.5
100	300	0.5	2200	215	4.0
200	330	0.5	. 2300	210	6.0
300	270	0.5	2400	210	6.5
400	360	1.0	2500	215	6.0
500	185	1.5	2600	235	4.0
600	200	3.5	2700	230	3.5
700	250	1.0	2800	225	4.0
800	295	2.0	2900	285	3.0
900	300	2.0	3000	270	3.5
1000	300	2.0	3100	275	3.0
1100	245	2.0	3200	270	4.5
1200	260	1.5	3300	295	6.0
1300	255	1.0	3400	295	6.0
1400	205	2.5	3500	295	7.0
1500	220	4.5	3600	305	6.5
1600	195	2.0	3700	305	7.5
1700	225	3.0	3800	305	9.0
1800	215	4.0	3900	315	12.0
1900	225	4.0	4000	325	14.0
2000	210	3.0	4100	320	12.0

TABLE II. PILOT-BALLOON-MEASURED WIND DATA, RELEASE NO. 3
RELEASED FROM LC-39, AT 1123 MDT/5 OCTOBER 1977
14821A LANCE, MISSILE NO. 3294, ROUND NO. 301 APL

### PIBAL RELEASE POINT WSTM COORDINATES:

X = 530,938.82 Y = 186,564.96 Z = 4,063.75

APPROXIMATELY: 1.5 MILES SOUTH OF LAUNCHER.

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
4200	325	11.0
4300	325	10.0
4400	325	10.0
4500	335	11.0
4600	340	12.0
4700	335	10.0
4800	335	10.0
4900	345	10.0
5000	340	9.5
5100	345	11.0
5200	345	9.0
5300	350	10.0
5400	345	10.5
5500	350	10.0
5600	350	10.0

HEIGHT (FEET)	DIRECTION (DEGREES)	(MPH)
5700	345	9.0
5800	345	6.0
5900	340	7.0
6000	345	7.0
6100	330	6.0
6200	335	7.0
6300	335	6.0
6400	330	4.0
6500	325	3.0
6600	320	3.0
6700	320	3.5
6800	335	4.5
6900	325	3.0
7000	335	3.0

TABLE II. (CONT)

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
SUR	200	3.0
100	180	2.5
200	165	4.0
300	190	1.5
400	000	0.0
500	190	2.0
600	160	2.5
700	030	1.0
800	060	1.0
900	130	2.5
1000	175	4.5
1100	175	3.0
1200	190	2.0
1300	195	3.0
1400	210	5.0
1500	215	7.5
1600	300	3.0
1700	295	2.5
1800	245	2.0
1900	290	1.5
2000	305	3.5

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
2100	240	2.5
2200	225	3.0
2300	240	4.0
2400	215	6.0
2500	230	4.0
2600	215	4.0
2700	230	4.5
2800	260	3.5
2900	250	4.0
3000	270	4.0
3100	285	6.0
3200	290	7.5
3300	305	9.0
3400	315	9.0
3500	315	9.0
3600	310	10.0
3700	310	10.0
3800	315	11.0
3900	315	12.0
4000	320	11.0
4100	315	9.0

TABLE III. PILOT-BALLOON-MEASURED WIND DATA, RELEASE NO. 4
RELEASED FROM CL-39, at 1133 MDT/5 OCTOBER 1977
14821A LANCE, MISSILE NO. 3294, ROUND NO. 301 APL

#### PIBAL RELEASE POINT WSTM COORDINATES:

X = 530,938.82 Y = 186,564.96 Z = 4,063.75

APPROXIMATELY: 1.5 MILES SOUTH OF LAUNCHER.

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
4200	320	9.0
4300	330	9.0
4400	335	9.0
4500	335	11.0
4600	340	10.0
4700	340	11.0
4800	340	9.0
4900	340	10.0
5000	340	10.0
5100	340	10.0
5200	345	9.0
5300	350	9.0
5400	350	10.0
5500	350	10.0
5600	350	9.0
5700	345.	8.0
5800	345	7.0
5900	345	7.0
6000	345	7.0
6100	340	6.5
6200	345	5.0
6300	335	6.0
5400	330	3.0
6500	330	3.5

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
6600	325	2.0
6700	310	2.5
6800	315	2.0
6900	340	4.0
7900	335	4.0
7100	330	4.0
7200	335	4.5
7300	335	4.0
7400	325	4.5
7500	330	5.0
7600	310	4.5
7700	320	6.0
7800	325	5.0
7900	335	5.0
8000	330	6.0
8100	325	5.5
8200	330	6.0
8300	315	6.0
8400	330	7.0
8500	310	6.0
8600	320	6.0
8700	330	6.5
8800	315	6.0
8900	320	6.0

TABLE III. (CONT)

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
9000	320	5.0
9100	320	5.0
9200	320	5.5
9300	330	5.0
9400	320	4.0
9500	315	4.0
9600	315	3.5
9700	325	6.0
9800	315	5.0
9900	290	3.5
10000	315	3.0
10100	310	4.0
10200	260	2.5
10300	315	3.0
10400	290	3.5
10500	265.	2.5

HEIGHT (FEET)	DIRECTION (DEGREES)	SPEED (MPH)
10600	275	3.5
10700	300	4.5
10800	300	4.0
10900	270	3.0
11000	290	4.0
11100	270	5.5
11200	260	6.0
11300	265	6.5
11400	260	5.5
11500	270	6.0
11600	290	7.5
11700	265	7.0
11800	275	6.5
11900	280	5.5
12000	275	4.0

TABLE III. (CONT)

# SIGNIFICANT LEVEL DATA 2780020723 WHITE SANDS TABLE IV.

GEODETIC COORDINATES 32.40043 LAT DEG 106.37033 LON DEG

REL.HUM. PERCENT	74. 873. 873. 874. 877. 8	
RATURE DEWPOINT CENTIGRADE	11111111111111111111111111111111111111	
TEMPE AIR DEGREES	10111111111111111111111111111111111111	
E GEOMETRIC ALTITUDE S MSL FEET	3969.0 4317.0 5064.9 7047.4 7047.4 10438.3 11353.7	1060
PRESSURE MILLIBARS	8822-8 8722-8 8722-8 7731-8 7733-8 5500-0 8500-0 8500-0 8315-8 8310-8 8310-8 8310-8 8310-9 8310-9 8310-9 8310-9	

MSL	
FEET RS MOT	
3989,00 FEET 1045 HRS MDT	3
ALTITUDE	NO. 723
STATION ALTITUDE	ASCENSION

SIGNIFICANT LEVEL DATA 2780020723 WHITE SANDS TABLE IV. (CONT)

GEODETIC COORDINATES 32.40043 LAT DEG 106.37033 LON DEG

PRESSURE GEOMETRIC TEMPERATURE REL.HUM.
ALTITUDE AIR DEWPOINT PERCENT
MILLIBARS MSL FEET DEGREES CENTIGRADE

ALTITUDE AIR DE LLIBARS MSL FEET DEGREES CEI 112.8 52051.0 -72.4 100.0 54351.3 -74.6 70.0 61216.2 -69.1 63.3 63205.7 -63.4 54.8 66114.9 -63.4 55.4 43.8 70732.6 -55.4 55.6 53.0 73127.6 -55.6

STATION ALTITUDE	TUDE 3989.00	E 3989.00 FEET MSL
. 77	1045	1045 HRS MDT

UPPER AIR DATA	WHITE SANDS	TABLE V.

GEODETIC COORDINATES 32.40043 LAT DEG 106.37033 LON DEG

INDEX OF REFRACTION	.0003	1.000312	.0003	.0002	.00029	.0002A	•0005	.00027	.000	.00025	.000	•0005€	•	.00023	.00023	.00022	.00021	.00021	.00021	•0002n	.00020	2	.00019	.0001A	.0001A	.00017	.00017	.0001	.00014	.00016
SPEED KNOTS	••	•	1.0	2.0	3.0	0.4	5.9	8.8	N	11.9	0	9.1	9.1	8.7	8.1	6.9	5.8	5.5	5.3	5.5	4.4	3.2	3.3	4.6	6.9	7.9	9.8	8.3	8.4	8.8
WIND DATA DIRECTION SPEED DEGREES(IN KNOTS	•						•			•	•		•		•		•				•	569.6								
SPEED OF SOUND KNOTS			8	9																		647.8						641.8		4.659
DENSITY S GM/CUBIC METER	036.	-	025.	013.																		772.6								
REL . HUM. PERCENT	74.0				•															•		66.3		•					•	•
ERATURE DEWPOINT CENTIGRADE	9	9	t	3	13.1	N	-	-	8.7	7.4	6.9	4.9	5.8	5.3	4.6	3.3	2.1	1.4	.7	0.	-1.4	-3.1	-5.0	9	-	N	8	0.6-	=	t
TEMPERATU AIR DEWP DEGREES CENTI	21.1	21.1	19.4	-	16.8	5	5	+	+	3	3	-		6								2.5			<b>.</b>	1		-2.3	3	•
PRESSURE MILLIBARS	882.8	882.5	867.2	852.0	836.9	822.0	807.5	793.1	779.0	765.0	751.2	737.6	724.3	711.3	4.869	685.7	673.1	2.099	9.849	636.6	624.8	613.1	601.7	590.4	579.3	568.4		547.0		
GEOMETRIC ALTITUDE MSL FEET	3989.0	0.000%			5500 • 0		6500 • 0		7500.0				9500.0	.0000	0500		1500.	2000	2500.	3000.	3500.	14000.0	4500.	5000	5500.	.0009	6500.	17000.0	7500.	18000.0

5 OCT 77 10/5 UPS VIN	SIALLON ALIL	STATION ALIITUDE 3989.00 FEET MSL	FEET MSL	
	5 OCT. 77	1045 H	RS MDT	

UPPER AIR DATA	0	WHITE SANDS	TABLE V. (CONT)

TES	DEG	DE6
GEODETIC COORDINATES	32.40043 LAT DEG	Con
000	2043	7033
TIC	32.4(	106.37033
EODE	۲,	=
•		

INDEX OF REFRACTION	1.000158	1.000153	-	1.000144	1.000137	1.000135	1.000134	1.000134	1.000133	1.000130	1.000126	1.000123	1.000121	=	=	=	1.000112	=	1.000108	1.000106	1.000105	1.000103	1.000100	1.000098	0	1.000094	1.000093
DATA SPEED KNOTS	10.7	11.6	•	13.9		•		59.6	31.7	•		35.4													1		'n
WIND DA DIRECTION DEGREES(TN	257.6	247.6	-		258.6		256.3	252.4	249.5	247.8	247.7	248.8			248.0	247.6		247.1			549.4		251.0	252.0	254.1	255.5	255.0
SPEED OF SOUND KNOTS	38.	635.3	•	630.8			626.6		624.3	623.1	651.9	620.6	419.4	618.1	616.7	615.2	613.7	612.2	610.8	609.3	407.7	606.2	605.7		603.7		601.0
DENSITY GM/CUBIC METER	670.3			609.8					562.9																459.9		
REL.HUM. PERCENT	39.1	53.0	50.3	35.9	21.4	30.3	43.6	62.5	81.4	72.6	<b>†•09</b>	52.6	44.7	36.8	35.5	37.7	0.04	45.2		8.94		41.3	18.7	16.8	14.9**		11.1**
SE SINT			18.	-22.6		27.		21.	19.	21.	24.				33.		34.	35.	35.	-36.4	37.	39.		48.	-50.7	52.	55.
AIR DEWPC	5.5		•	-10.4	i	-13.6	-14.7	-15.7	-16.7	-17.6	-18.5	-19.5	-20.5	-21.5	-22.7	-23.9	-25.1	-26.3	-27.4	-28.6	-29.9	-31.1	-31.4	-32.1	-33.0	-34.1	-35.5
PRESSURE MILLIBARS	516.3	496.5		458.8		-			415.0																		283.6
GEOMETRIC ALTITUDE MSL FEET	19000.0	20000-0	20500.0	21500.0	22000.0	22500.0	23000.0	23500.0	24000.0	24500.0	2500000	25500 • 0	2600000	26500.0	27000.0	27500.0	28000.0	28500.0	29000.0	29500.0	3000000	30500.0	31000.0	31500.0	32000.0	32500.0	33000.0

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

DOLLINE NOTING	C 2203 00 FEET MIST	210012
5 oct. 77	5 OCT. 77 1045 HRS MDT I	MHITE

	GEODETIC COORDINATES	32.40043 LAT DEG	106.37033 LON DEG
UPPER AIR DATA	2780020723	WHITE SANDS	TABLE V. (CONT)

INDEX OF REFRACTION	1.000091	•	.0000	•		1.000083		•	1.000079	•	1.000076	1.000075	1.000074	1.000072	1.000071	1.000070	1.000048	1.000067	1.000066	1.000045	1.000063	1.000062	1.000061	.00006	1.000059	.0000	.0000		.0000	.00005
DATA SPEED V) KNOTS	53.4	53.3	24.0	S	5	55.1	-	O	0	-	œ	S	59.1	-	a	N	N	3	3	S	~	0	a	9	-	0	~	-	3	#
WIND DA DIRECTION DEGREES(TN)	252.7	247.0			•	245.9	•	•		•		•	•	•		•	•	•	•	•		•				•			262.0	•
SPEED OF SOUND KNOTS	9.669	98.	596.8	95.	594.1	592.6	591.0	589.5	587.9	586.2	584.6	582.9	581.3	579.6	578.0	576.4	574.9	573.5	572.0	0	569.0	~	566.0	564.5	562.9	561.4	559.9	S	557.4	S
DENSITY S GM/CUBIC METER	407.9					373.9	•	•																						
REL.HUM. PERCENT	9.1**		5.2**		1.4**																									
TEMPERATURE R DEWPOINT EES CENTIGRADE	-57.4		-63.3																											
TEMF AIR DEGREES	-36.3	1	-38.4	6	9.04-	-41.8		2.44-		1.94-		:	-50.5	-51.8		•	:	:	-57.6	:		-61.0		-63.2		-65.5			-68.5	6
PRESSURE MILLIBARS	277.4		265.4			248,4	245.8	237.3	231.9	556.6	221.4	216.3	211.3	206.4	201.7	196.9	192.1	187.5	182.9	178.5	174.2	170.0	165.8	161.8	157.9	154.1	150.3	146.5	142.8	139.5
GEOMETRIC ALTITUDE MSL FEET	33500.0	34000.0	34500.0	35000.0	35500.0	36000.0	36500.0	37000.0	37500.0	38000.0	38500.0	39000.0	39500 • 0	4000000	40500.0	41000.0	41500.0	42000.0	42500.0	43000.0	43500.0	0.000++	44500.0	45000.0	45500.0	0.00094	46500.0	47000.0	47500.0	4800000

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

JETIC COORDINATES 32.40043 LAT DEG 106.37033 LON DEG	INDEX OF REFRACTION	1.000052	.00000	1.000050			1.000047		1.000044	1.000043	1.000042	1.000041	1.000040	1.000039	1.000038	1.000037	1.000036	1.000035	1.000034	1.000033	1.000032	1.000031	1.000030	1.000029	0000	1.000028	0000	.0000	1.000025	0000	• 0000
GEODETIC 32.4 106.3	SPEED KNOTS	8		4.89	65.9	200	50.1	40.4	39.0	36.4	35.1	35.4	36.0	37.1	37.3	36.0	34.5	30.5	26.0	22.1	18.4	16.6	16.1			5			5.7		
	WIND DATA DIRECTION S DEGREES(TN) K	260.4	259.2	258 1	258.1	6.867	260.3	9.797	564.6	265.7	266.4	266.3	266.3	266.2	266.5	267.3	268.3	270.2	272.9	576.6	282.0	286.4	289.5	290.3	287.2	283.9	279.0	271.4	261.7	05.	78.
R DATA 3723 ANDS (CONT)	SPEED OF SOUND KNOTS	554.8	53.	552.3	551.0	549.1		550.4	:	-	0	550.1	549.4	549.1		550.2		51.		52.	53.	553.5	54.	554.6	55.	555.7	56.	57.	559.6	61.	63.
UPPER AIR DAT 2780020723 WHITE SANDS TABLE V. (CONT)	DENSITY S GM/CUBIC METER	232.9	228.0	223.3	218.6	214.0	209.1	202.0	196.4	191.6	187.1	182.7	178.4	174.0	169.2	164.5	160.0	155.6	151.3	147.1			135.3		127.9	124.4	21.	17.	113.6	10	.90
	REL . HUM. PERCENT																														
3989.00 FEET MSL 1045 HRS MDT	TEMPERATURE AIR DEWPOINT DEGREES CENTIGRADE	-70.3	-	-72.2	-73.1	-/4-1	:	3	5	5	3		-74.3	•	-74-1		•		N	-72.1	:		-70.9	-70.5	-70.1	-69.1	-69.3	-68.3	6.99-	-65.4	0.49-
DE 396	PRESSURE MILLIBARS D	135.6		N	3	122.5	119.5	110.1	113.1	110.2	107.3	104.6	101.9	99.5	2.96	2.46	91.8	4.68	87.1	6.48	82.7	90.6	78.5	76.5	74.6	72.7			1.	9•59	+
STATION ALTITUS OCT. 77 ASCENSION NO.	GEOMETRIC ALTITUDE MSL FEET	48500.0	0.00064	49500.0	0.00000	0.00000	0.00010	0.00010	-			-	54000.0	54500.0	-			56500.0	57000.0	57500.0	58000.0	58500.0	2900000		0.00009	0.00509	61000.0	01500.0	62000.0	62500.0	53000.0

	UPPER A1
ATION ALTITUDE 3989.00 FEET MSL	278002
5 OCT. 77 1045 HRS MDT [	WHITE S
CENSION NO. 723	TABLE V.

TES DEG DEG		6	2	2	1	1	0	0	6	8	8	1	1	1	9	9	9	2	2	t	<b>t</b>
GEODETIC COORDINATES 32.40043 LAT DEG 106.37033 LON DEG	INDEX OF REFRACTION		1.000022			1.00002	1.000020	1.000020	•	1.000018	1.000018	1.00001	•	1.00001	1.000016	1.00001	1.000016	1.00001	1.000015	1.000014	1.00001
GEODETI 32. 106.	SPEED KNOTS	4.9	4.6	13.4	17.3	14.7	S	9.5	7.7	6.8			2.1	.2	2.8						
	WIND DATA DIRECTION SP DEGREES(TN) KN	190.2	200.4	211.7	217.7	224.9	235.0	255.0	291.1	318.8	359.3	75.5	75.4	526.9		95.					
R DATA 0723 ANDS (CONT)	SPEED OF SOUND KNOTS	564.6		•	566.5		•	4.695	571.2	573.1	574.9	574.1	573.4	572.6	571.9	571.1	571.2	572.0	572.8	573.6	574.4
UPPER AIR DATA 2780020723 WHITE SANDS TABLE V. (CONT)	DENSITY S GM/CUBIC METER	103.5	100.7	98.0	95.4	92.9	h.06	87.7	85.1	85.5	80.0	78.3	76.6	75.0	73.4	71.8	70.1	68.2	4.99	9.49	65.9
	REL . HUM. PERCENT																				
89.00 FEET MSL 1045 HRS MDT <sup>f</sup>	TEMPERATURE AIR DEWPOINT DEGREES CENTIGRADE	-63.1	-62.6	-62.2	-61.7	-61.2	-60.7	-59.5	-58.2	-56.8	-55.4	-56.0	-56.5	-57.1	-57.7	-58.2	-58.2	-57.6	-57.0	-56.4	-55.8
UDE 39,	PRESSURE MILLIBARS D	62.4	6.09	59.4	57.9	56.5	55.1	53.8	52.5	51.5	50.0	48.8	47.6	46.5	45.4	44.3	43.2	42.2	41.2	40.2	39.5
STATION ALTIT 5 OCT. 77 ASCENSION NO.	GEOMETRIC ALTITUDE MSL FEET	63500 • 0	0.00049	64500.0	65000.0	0.00559	0.00099	0.00599	0.00029	67500.0	0.00089	68500 • 0	0.00060	0.00569	7000000	70500.0	71000.0	71500.0	72000.0	72500.0	73000.0

WIND DATA DIRECTION SPEED DEGREES(T ) KNOTS	203.0 259.2 305.7 305.6 305.6 268.4 268.4 278.9 249.8 247.1 247.1 247.1 247.1 247.1 245.7 245.7 245.7 245.7 255.6 67.8 266.2 2
REL . HUM. PERCENT	881. 891. 73. 73. 73. 740. 16.
TEMPERATURE R DEWPOINT EES CENTIGRADE	11111 4 111111 9 4 3 4 3 4 3 4 5 6 5 5 6 5 6 5 6 5 6 5 6 6 6 6 6 6 6
TEMP AIR DEGREES	111 121 121 131 131 131 131 131 131 131
PRESSURE GEOPOTENTIAL ILLIBARS FEET	5064. 8548. 10438. 12445. 14577. 16867. 19332. 22000. 24919. 21759. 35898. 40738. 40738. 40738. 661467. 58761. 61366.
PRESSURE 6 MILLIBARS	850 750 700 700 650 650 650 650 650 650 650 6

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

6E00	
DATA	
SIGNIFICANT LEVEL DATA 2780040219	STALLION TABLE VII.

REL . HUM . PERCENT	24 34 34 34 34 34 34 34 34 34 34 34 34 34
RATURE DEWPOINT CENTIGRADE	
TEMPER AIR DEGREES C	11111 + 11121 11111 + 111311 11111 + 111311 111111 + 11131 111111 + 11131 11111 + 11131 1
GEOMETRIC ALTITUDE MSL FEET	4940.0 5050.9 6961.8 8175.9 10439.4 115342.3 14370.0 15141.1 15907.0 1925.3 18737.9 1925.3 18737.9 1925.8 1925.3 18737.9 1925.3 18737.9 1925.8 18737.9 1925.8 18737.9 1925.8 18737.9 1925.8 1925.8 18737.9 1925.8 1925.9 1925.8 1925.9 19
PRESSURE MILLIBARS	50000000000000000000000000000000000000

FEET MSL	HRS MDT
49	9 1129
ALTITUDE	
STATION	S OCT. 77 ASCENSION NO.

DATA			2
SIGNIFICANT LEVEL	2780040219	STALLION	TARLE UTT. (CONT)

REL.HUM.	PERCENT
ERATURE	AIR DEWPOINT DEGREES CENTIGRADE
TEMP	AIR DEGREES
GEOMETRIC	ALTITUDE MSL FEET
PRESSURE 6	MILLIBARS M

AIR DEWPOINT	ENTI				-65.6						
ALTITUDE	MSL FEE	7121.	8406.	9446	60967.1	2283.	7729.	9093.	8336.	6875.	2002
KESSUKE	ILLIBARS	3	6	+	20.07	5		.9			c

STATION ALTITUDE 4940.00 FEET MSL
1129 HRS MDT

UPPER AIR DATA 2780040219 STALLION TABLE VIII.

INDEX OF REFRACTION	1.000291	1.0002A2 1.0002A0 1.000277		1.000239	1.000229	1.000221	1.000218	1.000212	1.000202	1.000197		.0001		1.000182	-	1.000174	1.000172	000	0000	• 000
SPEED KNOTS	5.0		7.5	13.8	U TU	101	7.8 8.1	9 6	8.4	7.5	7.7	7.8	8.0	•	9.5		3	5	16.1	16.7
WIND DATA DIRECTION SP DEGREES(IN) KN	150 • 0		319.1	346.4	329-1	317.4	306.2	276.2	256.8	241.7	235.9		241.5	•	:	235.3	*	-	250.5	m
SPEED OF SOUND KNOTS	671.3	667.4	663.6	660.1	657.4	654.7	653.5	651.1	648.6	647.4	644.8	443.4	641.9	640.3	639.3	638.0	636.6	635.2	634.2	634.5
DENSITY S GM/CUBIC METER	1001-1	975.4	952.4	911.8	886.2	861.4	848.7	823.8	799.6	787.8	764.7	753.4	742.7	732.1	720.4	709.3	-			663.4
REL.HUM. PERCENT	56.8	59.6 72.2	77.6	52.6	52.5	54.4	57.8	4.49	63.3	57.2	56.2	2.09			74.3				29.7	•
TEMPERATURE R DEWPOINT EES CENTIGRADE	mad	12.0	9.3	0 ± 0	1.64		† · ·	9.1.	-3.0	9.4-	-7.5	9.7-	-7.0	6.9-	-8.3	-8.9	-9.5	6.6-	-14.9	-23.3
TEMP AIR DEGREES		18.5	15.1	12.8	10.6	9.4	6.3	5.4	3.3	2.3	. 2	-1.0	-2.3	-3.6		•	•		-8.5	•
PRESSURE MILLIBARS	853.2	821.9 821.9	793.2	751.4	724.5	698.4	685.6	648.4	636.3	624.4	601.3	280.0	578.8	567.8	556.9	246.2	535.6	525.3	515.1	505.1
GEOMETRIC ALTITUDE MSL FEET	600000	5500.0 6000.0 6500.0	7000-0	8500.0	9500.0	10500.0	11000.0	12500.0	13000.0	13500.0	14500.0	15000.0	15500.0	16000.0	16500.0	17000.0	17500.0	W	18500.0	O.

INDEX OF REFRACTION	1.000149	.000	•	.00014	.0001	•	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0001	.0000	.0000	.0000	.0000	.0000	.0000
DATA SPEED N KNOTS	16.6	16.8		8	19.5	-	M	2		0	S	3	വ	~	0	3	9	σ	-	N	S	m	t	9	9	-	3	2	~
WIND DA DIRECTION DEGREES(TN)	265.5	::	N	N	266.5	0	N	3	a	0	0	3	0	~	t	0	9	ŧ	3	3	S	~	9	9	9	9	249.7	9	0
SPEED OF SOUND KNOTS	634.0		6	628.2	456.7	625.2	3	'n					614.2						4.709		604.8			40109			597.9	.9	595.2
DENSITY S GM/CUBIC METER	651.3	31.	21.	å	602.6		+	2		-	6	:	3	t	5	D	9	8		å	3	2	2	6	:	3	S	8	-
REL.HUM. PERCENT	24.4	26.2	27.1	28.1	29.0	59.9	30.8	31.7	32.6	33.5	34.1	34.5	34.8	34.4	33.2	31.9	30.7	35.7	55.0	78.2	62.1	45.7	59.6	36.4	43.6	36.9	30.1	24.3**	18.6**
TEMPERATURE R DEWPOINT EES CENTIGRADE	-25.2	0	-	-	å	6	0	ò	:	3	3	+	5	9		8		6	•	3		:	5	÷	3	.9	8	:	+
TEMP AIR DEGREES	80 0		12.	3	÷	2	•	8	6	20.	21.	23.	54.	25.	.9	27.	8	6	:	-	5	3	3	+	.9	.9	:	8	
PRESSURE WILLIBARS	495.1	475.6	466.1	456.8	447.7	438.8	430.0	451.4	413.0	404.8	396.6	388.4	380.4	372.5	364.7	357.0	349.6	345.2	334.9	327.8	320.8	313.9	307.2	300.5	294.0	287.6	281.3	275.1	269.0
GEOMETRIC ALTITUDE MSL FEET	19500.0	20500•0	21000.0	21500.0	22000.0	22500.0	23000.0	23500.0	24000.0	24500.0	25000.0	25500 • 0	26000.0	26500.0	27000.0	27500.0	28000.0	28500.0	2900000	29500 • 0	3000000	30500.0	31000.0	31500.0	32000.0	32500.0	33000.0	33500.0	34000.0

GEODETIC COORDINATES 33.81920 LAT DEG 106.66501 LON DEG

UPPER AIR DATA 2780040219 STALLION TABLE VIII. (CONT)

> STATION ALTITUDE 4940.00 FEET MSL 5 OCT. 77 1129 HRS MDT ASCENSION NO. 219

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

STATION ALTITUDE 4940.00 FEFT MSL	UPPER AIR DATA
F OCT 27	NOT INTO
S OCI . //	SIALLION
ASCENSION NO. 219	TABLE VIII. (CONT

STATION ALTIT 5 OCT. 77 ASCENSION NO.	ALTITUDE 4940.00 FEET MSL 77 1129 HRS MDT N NO. 219	40.00 FEET 1129 HRS MDT	ET MSL MDT		2780040219 STALLION TABLE VIII. (CON	19 (CONT)		GEODETIC 33.8 106.6	DETIC COORDINATES 33.81920 LAT DEG 106.66501 LON DEG	
GEOMETRIC ALTITUDE MSL FEET	PRESSURE MILLIBARS	TEMI AIR DEGREES	TEMPERATURE R DEWPOINT EES CENTIGRADE	REL.HUM. PERCENT	DENSITY SGM/CUBIC	SPEED OF SOUND KNOTS	WIND DA DIRECTION DEGREES(TN)	DATA J SPEED J) KNOTS	INDEX OF REFRACTION	
34500.0		-40.7		12.9**	394.3	593.9			1.000088	
35000.0		-41.8	-63.6	7.2**	387.3	592.6			1.000086	
35500.0		-42.8		1.5**	380.4	591.2			1.000085	
36000.0		0.44-			373.6	589.7			1.000083	
36500.0	240.1	-45.2			366.9	588.2	249.7	72.7	1.000082	
37000.0		1.91-			360.4	586.6		•	1.000080	
37500.0		-47.6			354.0	585.1			1.000079	
38000.0		-43.8			347.7	583.5		•	1.000077	
38500.0		-50.0			341.6	581.9		•	1.000076	
39000.0		-51.2			335.5	580.3			1.000075	
39500.0		-52.5			329.6	578.7	•	•	1.000073	
400000		-53.7			323.8	577.2		•	1.000072	
40500.0	199.3	6.45-			318.0	575.6		•	1.000071	
41000.0		-56.0			311.9	574.1		•	1.000069	
41500.0		-57.1			305.8	572.7			1.000068	
42000.0		-58.2			299.9	571.2	253.7		1.000067	
42500.0		-59.3			294.1	569.7		•	1.000066	
43000.0		4.09-			288.5	568.3			1.000064	
43500.0		-61.5			282.9	566.8	255.9	•	1.000063	
0.00044		-62.6			277.5	565.3	256.0		1.000062	
44500.0		-63.7			272.2	563.8			1.000061	
45000.0		8.49-			266.9	562.3	256.2		1.000059	
45500.0		-62.9			261.8	560.8			1.000058	
46000.0	152.0	0-19-			256.8	559.3	256.7	4.68	1.000057	

WAS USED IN THE INTERPOLATION. AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE \*

1.000051

.0000053

86.6 84.2 80.4 76.5

257.6 257.7 258.0 258.3

554.6 553.5 553.5 553.5

242.0 236.8 230.8 224.9

1.000054

1.000056 .00000

89.4 89.4 88.4

257.2

556.2

546.9

45000.0 45500.0 0.00094 46500.0 47000.0 47500.0 4800000 48500.0 0.00064

-69.3

-68.1

152.0 148.2 144.5

-71.3 -70.5

140.8 137.2 133.7 130.3

560.8 559.3 557.8

256.8

ETIC COORDINATES 33.81920 LAT DEG 06.66501 LON DEG	INDEX OF REFRACTION	1.000049	1.000045	1.000041	1.000038 1.000037 1.000035	1.000035 1.000034 1.000033 1.000032	1.000031 1.000030 1.000029 1.000029	1.000028 1.000027 1.000025 1.000025 1.000024 1.000024 1.000023
GEODETIC 33.8 106.6	DATA SPEED D KNOTS	1:0:	54.7 52.5	44.1	33.50	24.13	21.8 19.3 17.2 15.1	13. 10. 10. 10. 10. 10. 10. 10. 10. 10. 10
		259.6 261.2 263.1	265.3 267.1 267.6	268.0 268.0 267.9	268.7 268.9 268.9	268.9 268.6 268.2 267.8	267.4 267.6 269.1 271.1	275.6 281.2 282.8 282.8 276.9 265.0 249.8 249.8
ATA 19 (CONT)	SPEED OF SOUND KNOTS	553.5 553.5		:::	2000	550.2 550.2 550.2 552.0	554.3 556.2 555.9 555.7	559 559 561 561 563 563 564
UPPER AIR DATA 2780040219 STALLION TABLE VIII. (CON	DENSITY S GM/CUBIC METER	219.1 213.5 208.1	v œ m a	136	170.9	50000		000000000000000000000000000000000000000
	REL.HUM. PERCENT							
FEET MSL S MOT (	TEMPERATURE AIR DEWPOINT GREES CENTIGRADE		10 <b>(</b> 0 0 0 1 1	o o o	0 ~ ~ ~	t 7 7 7 .	<b>~</b> 10 10 <b>~</b>	10000c015
40.00 F	OE				73.7	-73.7 -73.7 -73.7	-70.7 -69.3 -69.5	666666666666666666666666666666666666666
ALTITUDE 4940.00 FEET 177 1129 HRS MDT	PRESSURE MILLIBARS		117.5	105.3	95.			
STATION AL 5 OCT. 77 ASCENSION	GEOMETRIC ALTITUDE MSL FEET	49500.0 50000.0 50500.0	51500.0 51500.0 52000.0	53000.0	54500.0 55000.0 55500.0	56000.0 56500.0 57000.0 57500.0	58000.0 58500.0 59000.0 59500.0	60000.0 60500.0 61000.0 62000.0 62500.0 63500.0

STATION ALIITUDE 4940.00 FEET MSL.
1129 HRS MDT

GEODETIC COORDINATES 33.81920 LAT DEG 106.66501 LON DEG	INDEX
GEODETIC 33.6 106.6	WIND DATA DIRECTION SPEED
UPPER AIR DATA 2780040219 STALLION TABLE VIII. (CONT)	REL.HUM. DENSITY SPEED OF PERCENT GM/CUBIC SOUND
LIITUDE 4940.00 FEET MSL. 7 1129 HRS MDT 1 NO. 219	PRESSURE TEMPERATURE AIR DEWPOINT

INDEX OF REFRACTION	1.000022	-	1.00002	1.00002	1.00001	1.00001	1.00001	1.00001	1.00001	1.00001	1.00001		1.00001	1.00001	1.00001	-	1.00001	1.00001	1.00001	1.00001	1.000	1.00001	1.00001	1.00001	1.00001	1.00001	1.000	1.00001	-	1.00001
DATA SPEED N KNOTS	7.7	7.4	7.1	7.2	7.3	6.5	5.7	5.3	5.1	6.4	0.4	3.8	4.4	5.7	6.9	6.5	5.6	0.9	7.8	9.6	11.0	12.2	13.6	13.4	n	n	12.2	-	10.7	11.1
WIND DA DIRECTION DEGREES(TN)	50	256.8	63	69	75	82	92	00	05	10	30	56	19.5	34.1	45.9	8.94	51.6	57.9	62.7	9•59	73.3	82.4	6.68	97.5	105.4	112.2	113.6	115.3	116.7	~
SPEED OF SOUND KNOTS	565.0	566.0		568.0								573.9				574.4					75.	75.	75.	75.	75.	75.		76.	576.2	76.
DENSITY GM/CUBIC METER		94.5					82.1					71.9				65.2						56.3					49.8		47.4	
REL.HUM. PERCENT																														
TEMPERATURE R DEWPOINT EES CENTIGRADE																														
TEMI AIR DEGREES	-62.8	-62.1	-61.3	9.09-	-59.9	-59.5	-58.4	-57.7	-57.1	-56.4	-56.2				-55.8		-55.6				-55.2				6.45-	-54.8	-54.7	-54.6		-54.5
PRESSURE MILLIBARS	58.7	57.2	55.8	54.5	•			49.3	48.2	47.0	45.9	44.8	43.7	42.7	41.7	40.7	39.7	38.8	37.9	37.0	36.1	35.2	34.4	33.6					29.8	
GEOMETRIC ALTITUDE MSL FEET	64500.0	000	65500.0	0.00099	66500.0	67000.0	67500.0	68000.0	68500 • 0	0.00069	69500.0	70000.0	70500.0	71000.0		72000.0	72500.0	73000.0	73500.0	74000.0		75000.0	75500.0	7600000	76500.0	77000.0	77500.0	78000.0	78500.0	7900000

_			
	_		
	S		
	Σ		
		10	
	-	는	
	1.1		
		~	
	u	23	
		=	
	0	1129 HRS MDT	
	0	0	
		2	
	0	-	
	+	-	
	7		
	₹.		-
	3		U.
			_
	w		a
	0		
	$\supset$		
	-		
	-		0
	-		7
		~	-
	=		-
	4	-	4
	-		0
	Z		-
	0	-	S
	-	U	Z
	-	0	141
	4	5 oct. 77	ü
	_	10	in
LYSI	10		-
	STATION ALTITUDE 4940.00 FEET MSL		ASCENSION NO. 219

JETIC COORDINATES 33.81920 LAT DEG 106.66501 LON DEG	INDEX OF REFRACTION		1.000009	1.000009	1.000008			1.000006 1.000006 1.000006 1.000005 1.000005 1.000005
GEODETIC 33.8 106.6	DATA SPEED D KNOTS		13.0	14.4	15.2	15.4	112000	7778888
	WIND DA DIRECTION DEGREES(TN)	117.8 116.4 113.8	1110.0	107.9 104.8 101.3	97.9 97.8 97.8	101.2 102.6 103.8	105.1 105.7 100.3 96.9	94.8 92.5 89.9 89.7 93.4 97.2
DATA 119 (CONT)	SPEED OF SOUND KNOTS	576 577 577			579.8 580.1 580.5	581 581 581 582	582. 583. 583.	584.9 585.3 585.7 586.1 586.9 586.9
UPPER AIR DA 2780040219 STALLION TABLE VIII. (G	DENSITY GM/CUBIC METER	45.1 44.0 42.9	41.9	37.9 9.7.9	3 4 4 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5 5	33333 3031 3031 3031 3031 3031	2000 2000 2000 2000 2000 2000 2000 200	00000000000000000000000000000000000000
	REL.HUM. PERCENT							
ET MSL OOT	TEMPERATURE R DEWPOINT EES CENTIGRADE							
40.00 FEET 1129 HRS MDT	TEMF AIR DEGREES	-53.7	522	52 52 51	-51.4	-50.4 -50.4 -49.8	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	148.0 1447.7 146.8 146.5 146.5
UDE 49	PRESSURE WILLIBARS	28.4 27.7 27.1	25.8 25.8	24.0	22222	19.9		111111111111111111111111111111111111111
STATION ALTIT 5 OCT. 77 ASCENSION NO.	GEOMETRIC ALTITUDE MSL FEET	79500.0 80000.0 80500.0	81500.0 81500.0 82000.0	83000.0 83500.0	84000.0 84500.0 85000.0	86000.0 86500.0 87500.0	88500.0 88500.0 89000.0 90000.0	90500.0 91000.0 91500.0 92500.0 93500.0 94000.0

GEODETIC COORDINATES 33.81920 LAT DEG 106.66501 LON DEG	INDEX OF REFRACTION	1.000005 1.000005 1.000005 1.000004
GEODET1 33. 106.	SPEED KNOTS	
	WIND DATA DIRECTION SI DEGREES(TN) KI	
ATA 19 (CONT)	SPEED OF SOUND KNOTS	21.5 587.7 21.0 588.1 20.5 588.4 20.0 588.8 19.5 589.2
UPPER AIR DATA 2780040219 STALLION TABLE VIII. (CONT)	REL.HUM. DENSITY SPEED OF PERCENT GM/CUBIC SOUND METER KNOTS	21.5 21.0 20.5 20.0 19.5
-	REL.HUM. PERCENT	
TT MSL.	PRESSURE TEMPERATURE R AIR DEWPOINT P MILLIBARS DEGREES CENTIGRADE	
0.00 FEE	TEMF AIR DEGREES	145.0 144.7 144.7
TITUDE 494	PRESSURE MILLIBARS	13.7
STATION ALTITUDE 4940.00 FEET MSL 5 OCT. 77 1129 HRS MDT ASCENSION NO. 219	GEOMETRIC PRESSURE ALTITUDE MSL FEET MILLIBARS	94500.0 95000.0 95500.0 96000.0

## MANDATORY LEVELS 2780040219 STALLION TABLE IX.

ATA SPEED KNOTS	5.5	3.1	14.0	10.0	7.6	7.7	10.5	16.6	19.4	31.5	47.0	57.1	72.0	83.1	84.1	89.2	9.59	39.0	18.6	9.5	7.8	5.3	5.3	11.0	14.6	15.6	
WIND DATA DIRECTION S DEGREES(TN) K	150.5	316.7	345.5	317.9	269.8	236.6	235.8	262.4	266.1	267.6	246.1	549.4	250.2	250.2	255.8	257.2	261.3	268.5	268.0	281.8	549.6	302.1	55.4	117.2	106.3	104.0	
REL . HUM. PERCENT	. 48	75.	51.	54.	67.	57.	75.	24.	29.	34.	31.	37.															
TEMPERATURE R DEWPOINT EES CENTIGRADE	12.0	11.6	5.9	-,3	•	-7.5	-8.8	-24.9	-28.4	-32.8	-39.9	-44.5													•		
TEMF AIR DEGREES	21.7	15.9	12.8	8.5	<b>t•t</b>		-5.1	-7.9	-14.2	-21.2	-28.0	-35.0	-43.1	-54.7	-60.7	-67.6	-71.3	-73.7	-69.5	-65.6	-63.4	-58.1	-55.7	-54.5	-52.6	-50.2	-46.5
PRESSURE GEOPOTENTIAL ILLIBARS FEET (	5050.	6762.	8553.	10441.	12438.	14563.	16829.	19267.	21923.	24816.	27999.	31578.	35681.	*06+0+	43255.	46351.	49902.	54210.	58500.	61123.	64204.	67925.	72574.	78603.	82451.	87206.	93422.
PRESSURE 6 MILLIBARS	850.0	800.0	750.0	700.0	650.0	0.009	550.0	200.0	450.0	0.004	350.0	300.0	250.0	200.0	175.0	150.0	125.0	100.0	80.0	70.07	0.09	20.0	0.04	30.0	25.0	20.0	15.0

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

REL.HUM. PERCENT	ď	6		ט ני	51.0	3.	5	+		0		•	5	-	8	5												
PERATURE DEWPOINT S CENTIGRADE	0	, -	11.4	 7.0	;:	-14.8	·	-26.7		is	8		-33.3	3.		•												
TEMPE AIR DEGREES	c	0			0	•		•	+		2	-26.6			:	1:	3	-	å	2		6	å	9	-56.1	-53.7	8	-45.5
GEOMETRIC ALTITUDE MSL FEET	0.1504		5154.4	 •	10446.2		0	~	M	10	10	28586.0	+	in	0	-	~	.0	+	m	01	m	-	_	58217.4	78860.3	37447.2	95444.2
PRESSURE MILLIBARS	4-6			 ) K	700.0	8.3	0.0	7.3	8.3	0.0	9.3	3.3	1.3	8.9	2.3	8.1	0.0	0.0	0.0	0.0	4.3	4.3	0.0	0.0	0.0	0.0	0.0	5.8

)ETIC COORDINATES 33.16712 LAT DEG .06.49511 LON DEG	DEX F ACTI	1.000290 1.000290	.000	1.000275	000	1.000243	000	1.000225	1.000220	1.000207	1.000201	1.000196	1.000185	1.000181	1.000179	1.000177	1.000175	1.000172	1.000170	1.000168	1.000165	1.000163	1.000160
GEODETIC 33.1 106.4	SPEED KNOTS	1.2			9.4	8.3	4.6	5.9	6.1	0.9	S. 3	t +	4.3	3.7	5.9	2.5	2.4	3.9	5.9	8.6	11.7	14.7	17.5
	WIN CTI ES(		200			t +	356.2	344.7				274.4			-	-						257.5	
DATA 382 (CONT)	ON F	00		+ 10	662.8		660.5	657.6	656.2		653.1	652.1			647.8			0.449	642.8	-	640.3	6	3
UPPER AIR DATA 2780030382 JALLEN TABLE XI. (CONT)	ITY UBIC ER	1019.7	994.3	967.6 953.0	937.3		894.2			831.8	819.1	794.1	781.9	770.0	758.2	746.7	735.4	_	-		-	681.5	-
	, R.	56.8 58.8	+0	NN	1	t c	53.8	-	0 0	S	001	90	3	t	1	0	N	2	8	-	4	47.3	
T MSL	OI GR	12.2		10.8				•		+	9	-10.6	3	+	14.	13.	13.						•
1.00 FEE	HE O		18.2	15.7	# :	14.3	13.1	0	9.8	8.1	7.3	5.0	2.0	4.1	3.0	1.9	8.	2	-1.3	-2.4	-3.5	-4.5	-5.6
ALTITUDE 4051.00 FEET 77 1130 HRS MDT N NO. 382	PRESSURE MILLIBARS	866.7 851.6	836.6 821.9		778.9		737.8	711.	698.	673.	•099		625	613.	601.	290	579.	568.	557.	546.	536.		
STATION ALTI	ETRI TUDE FEET	4500.0		0.000.0		8500.0	900000	100000	10500.0	11500.0	12000-0	12500.0	13500.0	14000.0	14500.0	15000.0	15500.0	160000.0	16500.0	17000.0	17500.0	18000.0	18200.0

33.16712 LAT DEG .06.49511 LON DEG	INDEX OF REFRACTION	1.000158 1.000150	00014	.00013	1.000125 1.000125 1.000123 1.000120	00000	000000	888888
GEODETIC 33.1 106.4	SPEED KNOTS		15.2		20 20 30 30 30 30 30 30 30 30 30 30 30 30 30			5000 5000 5000 5000 5000 5000
	WIND DAT DIRECTION DEGREES(TN)	259.8 258.5 256.5				249.4 247.7 246.3 246.3	2 5 6 6 6 8 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6	252.4 252.4 252.4 254.1
BATA 382 (CONT)	SPEED OF SOUND KNOTS	636.4 635.2 634.2		627.7 626.3 625.0	623.7 622.3 621.0 619.7	617.2 615.9 614.6 613.3	2001	604.3 601.5 600.2 598.9
UPPER AIR (278003036) JALLEN TABLE XI. (C	DENSITY SOM CONTRACTER	661.2 651.0 640.3	619.5 610.1 601.0	592.0 582.7 573.4	564.3 555.3 546.4 537.4	528.5 519.8 511.3 502.9	486.4 478.7 470.7 4562.7	
5	REL.HUM. PERCENT	53.0 52.1 43.1	25.0 20.1 15.8	100	0000	00000	222.6 602.3 43.0 33.6	2
T MSL DT	ERATURE DEWPOINT CENTIGRADE	-14.6 -15.7 -18.7			141.2	11001	11.8001	28
1.00 FEE	TEMPI AIR DEGREES	7.9-	-9.9	-13.6	-16.9 -18.0 -19.1	22.5 24.3 25.3 25.3	128.8 129.9 130.9	325 33 34 35 36 36 36 36
ALTITUDE 4051.00 FEET 77 NN NO. 382	PRESSURE MILLIBARS	506.5 496.8 487.2	468.4 459.1	441.2	415.1 406.8 398.6 390.4	382.4 374.5 356.8 359.2 351.9	344.5 330.2 323.2 316.3	203.0 203.0 289.9 277.4
STATION ALTI 5 OCT. 77 ASCENSION NO	GEOMETRIC ALTITUDE MSL FEET	19000.0	21500.0	22500.0 23000.0 23500.0	24000.0 24500.0 25000.0 25500.0	26000.0 26500.0 27000.0 27500.0 28000.0	28500.0 29000.0 29500.0 30000.0 30500.0	31500.0 32000.0 32500.0 33000.0

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.

C COORDINATES 16712 LAT DEG 49511 LON DEG	INDEX OF REFRACTION	1.000089 1.000088 1.000086				1.000076		1.000072	•		•		•	•		400			•00005	00.	.00000
GEODETIC 33.10	ATA SPEED KNOTS	62.1 64.0 66.0	86	70.2				72.5			•			•	78.4						-
	WIND DA DIRECTION DEGREES(TN)	254.9 254.0 252.4	t D	47.	45.	45.	16	47.	.64	50.	52.	54.	55.	56.	57.	57.	57.	57.	57	576	58.
DATA 382 (CONT)	SPEED OF SOUND KNOTS	597.5	93.	06		÷ 1		580.2				571.7		-		3	61.		59.	558.5	57.
UPPER AIR DA 2780030382 JALLEN TABLE XI. (CO)	DENSITY SGM/CUBIC	401.7	o t	: 0	+ 0	-10	6	+ 0	å	. 0	+	90	-	di	: 0	1	à	9	-	•	-
Ī	REL . HUM. PERCENT																				
ET MSL MDT	PERATURE DEWPOINT CENTIGRADE																				
51.00 FEET 1130 HRS MDT	TEMPE AIR DEGREES	-37.9		÷ 3	-46.7	-47.9		-51.3		-54.7	-56.8	-58.9	0.09-	-61.0	-63.1	-64.5	-65.3	-66.1	6.99-		-68.4
TUDE 409	PRESSURE MILLIBARS	271.3											70.	ė.	158.0		50.	46.	3.	39.	M
STATION ALTI 5 OCT. 77 ASCENSION NO	GEOMETRIC ALTITUDE MSL FEET	34000.0	35500.0		37500.0	390000		40500.0		41500.0			-	_	45500.0			000	20	8000	48500.0

ATES DEG DEG	2	LC.	671	147	140	540	240	141	040	138	137	136	135	134	34	33	132	30	661	821	0	101	0	125	0	0	
COORDINATES 6712 LAT DEG 19511 LON DEG	INDEX OF REFRACTION		1.0000	0	•		0.	•	1.000040	1.000038	1.0000	1.0000	1.0000	1.0000			•	1.0000				•	1.0000	1.0000	0	1.0000	1
GEODETIC CC 33.1671 106.4951	TA SPEED KNOTS		64.5	•	44.1			•								•											
	WIND DATA DIRECTION S DEGREES(TN) K		259.3			264.5		265.7		269.1					273.3						274.4	272.6			529.9		
DATA 382 (CONT)	SPEED OF SOUND KNOTS	56.	555.2	53.	55.	55.	54.	54.	53	52	53.	53.	. 49	54.	555.1	55.	500	57.	57.	58.	58.	59.	.69	.09	9	63.	
UPPER AIR DATA 2780030382 JALLEN TABLE XI. (CONT)	DENSITY GM/CUBIC METER	56.	221.5	11	000	. 46	.06	85.	181.3	72.	68.	63.	59.	24.	150.6	9	40	34.	31.	27.	+	20.	17.	•			
	REL.HUM. PERCENT																										
ET MSL DT	TEMPERATURE R DEWPOINT EES CENTIGRADE																										
1.00 FE	TEMF AIR DEGREES	-69-2	-70.8		-70.1		-70.3		-71.5		-71.6	-71.2	6.07-	-70.5	-70-1	1.69-	1000	-68.6			-67.5	-67.1	1-99-	-62.9	-65.1	-64.3	
ALTITUDE 4051.00 FEET 77 1130 HRS MDT NN NO. 382	PRESSURE MILLIBARS	32.	125.9		116.6	113.6			105.1		97.3				87.8			79.2	77.2	75.3	73.4	71.5		68.0	•	2.49	
STATION ALTITUS OCT. 77 ASCENSION NO.	GEOMETRIC ALTITUDE MSL FEET		50000.0	50500.0	51500.0	52000.0	52500.0	53000.0	54,000.0	54500.0	55000.0	55500 • 0	56000.0	56500.0	57000.0	0.00575	58500.0	5900000	59500.0	0.00009	60500.0	000	0	0	2500	00	4 4600

ETIC COORDINATES 33.16712 LAT DEG 06.49511 LON DEG	INDEX OF REFRACTION	0	.00000	20000		*00000	0	.00001	1.000019	.00001	.00001	00001	.00001	_	.00001		.00001	.00001	.00001	0000	.00001	.00001	.00001	.00001	.00001	.00001	.00001	.00001	000	.00001	1.000011
GEODETIC 33.1 106.4	DATA SPEED () KNOTS	1.3	4.8	8.6	12.4	4.0	-	15.6	0	N	0	15.1	0	9.1	8.9	0.6	9.6	10.5	11.4	11.1	8.7	6.3	3.5	9.5	19.5	29.7	28.4	25.7	23.1	16.4	6.7
	WIND DA DIRECTION DEGREES(TN)	146.5	6.46		83.0	•	252.3						255.8													20.07	9.69	8	6.79	6.59	-
382 (CONT)	SPEED OF SOUND KNOTS	565.1		567.2						•			574.3	574.5	574.6	574.8	574.9	575.1	575.2	575.4	575.5	575.7	575.8	576.0	576.1	576.3			576.7	76.	577.0
UPPER AIR DA 2780030383 JALLEN TABLE XI. (CC	DENSITY GM/CUBIC METER	d	99.1		93.6				•			77.2																	50.9		•
	REL.HUM. PERCENT																														
OT MSL	TEMPERATURE R DEWPOINT EES CENTIGRADE																														
1.00 FEE	TEMF AIR DEGREES	-62.7	-	-61.2	+.09-	-59.6	-58.8	-58.0	-57.2	-56.4						-55.5	55.							-54.6	-54.5				-54.0	-53.9	-53.8
ALTITUDE 4051.00 FEET 77 1130 HRS MDT NN NO. 382	PRESSURE MILLIBARS	61.6	0	58.6	57.2	55.8	54.4	53.1	51.8	50.5	49.3	48.2	47.0	45.9		43.7	45.7	41.7	40.7	39.7	38.8	37.9	37.0	36.1	35.3	34.4			32.0	31.3	•
STATION ALTI	GEOMETRIC ALTITUDE MSL FEET	0.00000	500	0	65500.0		0.00599	0.00029	67500.0	0.00089	68500 • 0	0.00069	0.00569	7000000	70500.0	71000.0	71500.0	72000.0	72500.0	73000.0	73500.0	2400000	74500.0	75000.0	75500.0	7600000	76500.0	77000.0	77500.0		78500.0

Mr.			
- 7			
2			
	15		
-	5		
m';	Σ		
W,	•		
4	2		
0	I		
0	0		
• (	7		
= :	3		
0			
#		N	
		8	
W		382	
5			
2			
-		o	
-		Z	
1	-	_	
4	-	Ž	
-		SCENSION NO.	
6	_	2	
H	U	z	
-	ō	W	
4		Ç	
STATION ALTITUDE 4051.00 FEET MSL	0	S	
U		-	

33.16712 LAT DEG .06.49511 LON DEG	INDEX OF REFRACTION	1.000011	1.000010	1.00010	1.000010	1.000009	1.000009	1.000009	1.000009	1.000008	1.000008	1.000008	1.000008	1.000008	1.000007	1.000007	1.000007	1.000007	1.000007	1.000007	1.000006	1.000006	1.000006	1.000006	•	1.000006	.00000	.00000	000.	000
GEODETIC 33.1 106.4	DATA SPEED N KNOTS	2		14.3	16.0		40.3	70.1		85.4	80.7	76.8	53.1	29.7	9.6	14.4	23.9	34.1	43.6	49.4	55.2	61.1	41.3	9	S	58.3	m	-	O	
	WIND DA DIRECTION DEGREES(TN)	78.	58.	248.0	++	-		80.3	80.1	80.9	81.7	82.7	85.6	93.2	138.7	213.7	227.9	233.9	236.7	237.3	237.7	238 • 1	230.5	180.9	8	87.1	3	0	8	
DATA 382 (CONT)	SPEED OF SOUND KNOTS	77.		578.0		579.2		580.0						582.4				583.9		584.4	584.7		585.2	585.4		585.9	586.1	586.4	586.6	586.9
UPPER AIR DATA 2780030382 JALLEN TABLE XI. (CONT)	DENSITY SGM/CUBIC	7.	46.1	9.0	8	1:		39.7	8	7	.9	35.9	2	34.2	3	N	-	0	0	9	8	0	1	.9		3	+	+	23.7	2
	REL . HUM. PERCENT																													
DT MSL	TEMPERATURE R DEWPOINT EES CENTIGRADE																													
11.00 FEE	TEMF AIR DEGREES	3	M	-53.0	-52.4	-52.1	-51.8	-51.5	-51.2	-50.9	-50.6	-50.3	-50.0	1.64-	4.64-	-49.1	-48.8	-48.5	-48.3	-48.1	6.24-	1-47-7	-47.5	4.7.4	-47.2	-47.0	8.94-		4.94-	-46.2
ALTITUDE 4051.00 FEET 77 1130 HRS MDT N NO. 382	PRESSURE MILLIBARS	29.8	29.1	27.8	27.1	26.5	•	25.3	24.7	24.1	23.5	23.0												•		16.6	.9	15.8		•
STATION ALTITS S OCT. 77 ASCENSION NO.	GEOMETRIC ALTITUDE MSL FEET	79000.0	79500.0	800000.0	81000.0	81500.0	82000.0	82500.0	83000.0	83500.0	84000.0	84500.0	85000.0	85500.0	86000.0	86500.0	87000.0	0.00570	88000.0	88500.0	89000 0	89500 • 0	900006	90500.0	91000.0	91500.0	92000.0	2500		3500.

GEODETIC COORDINATES 33.16712 LAT DEG 106.49511 LON DEG	SPEED OF KNOTS REFRACTION	1.000005
GĒ.	WIND DAT DIRECTION DEGREES(TN)	
OATA 32 CONT)	SPEED OF SOUND KNOTS	22.6 587.1 22.1 587.3 21.6 587.6
UPPER AIR DATA 2780030382 JALLEN TABLE XI. (CONT)	REL.HUM. DENSITY SPEED OF PERCENT GM/CUBIC SOUND METER KNOTS	22.6 22.1 21.6
5	REL.HUM. PERCENT	
ET MSL MDT .	TNT	
1.00 FE	TEMI AIR DEGREES	-46.0 -45.9 -45.7
TITUDE 405	PRESSURE TEMPERATURE AIR DEWPO) MILLIBARS DEGREES CENTIGE	14.8
STATION ALTITUDE 4051.00 FEET MSL 5 OCT. 77 1130 HRS MDT : ASCENSION NO. 382	GEOMETRIC PRESSURE ALTITUDE MSL FEET MILLIBARS	94000•0 94500•0 95000•0

# MANDATORY LEVELS 2780030382 JALLEN TABLE XII.

GEODETIC COORDINATES 33.16712 LAT DEG 106.49511 LON DEG

WIND DATA DIRECTION SPEED DEGREES(TN) KNOTS 60.4 .5 3.8 4.5 8.3 332.2 6.1 285.6 4.5 292.9 2.7 241.5 8.0 258.9 17.7 267.3 15.1 255.0 24.8 246.9 41.1	248.6 69.8 254.9 78.3 257.1 80.3 260.9 59.1 269.3 33.9 267.5 11.6 87.8 7.5 255.7 18.4 283.0 9.5 259.7 10.9 80.6 83.1
RFL.HUM.  PERCENT DI  59. 55. 55. 51. 58. 41. 58. 29. 41. 56. 10. 24.	
NA ADE 11199611	
S CENTER OF THE STATE OF THE ST	, o, t + o o t a o + + t v v
DEGRI 199 115 112 125 125 125 125 125 125 125 125	141111111111111111111111111111111111111
GEOPOTENT FEET 5053- 6754- 8549- 10447- 12456- 14597- 14597- 19349- 22020- 24934- 28154- 28154- 31763-	
PRESSURE GEOPOTENTIAL MILLIBARS FEET 850.0 5053. 800.0 6754. 750.0 10447. 650.0 12456. 600.0 14597. 550.0 14597. 550.0 22020. 450.0 22020. 450.0 22020. 450.0 22020. 450.0 22020.	250.0 200.0 175.0 125.0 100.0 80.0 70.0 70.0 50.0 20.0

\*\* AT LEAST ONE ASSUMED RELATIVE HUMIDITY VALUE WAS USED IN THE INTERPOLATION.